

Code: BCS-B-SP1602G-1SFP

SWITCH POE **BCS-B-SP1602G-1SFP** 16-PORT SFP BCS BASIC

Net: **219.24 EUR** Gross: **219.24 EUR**

Due to the reliability and ensuring high quality of transmission, the BCS-B-SP1602G-1SFP 16-port PoE switch is an ideal solution for applications in CCTV IP installations.



SPECIFICATION

LAN ports:	• 16 x RJ45 (16 x PoE (802.3af/at)), • 1 x Port Combo: SFP / RJ45 - Uplink, • 1 x RJ45 - Uplink
Transmission speed:	• 10 / 100 Mbps - 16 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 2 RJ45 (Uplink) ports, • 1000 Mbps - 1 Port SFP (Uplink)
Maximal output power:	30 W / port PoE
Maximal total power:	150 W
MAC addresses table:	8k
Management:	—
Operation modes:	• AI VLAN mode - 1 ... 16 ports are isolated from each other and separately work with the 17, 18 ports • AI EXTEND mode - ports 1 ... 8 support transmission up to 250 m (cat5e, cat6) @ 10 Mbps • AI QoS (Quality Of Service) mode - prioritization of video packets • AI PoE mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected - Watchdog PoE
Main features:	• (RJ45) 10/100/1000 Mb Auto-Negotiation, Auto MDI/MDIX • 4 operating modes: AI VLAN, AI EXTEND, AI PoE, AI QoS - selectable by switch • Power supply PoE - wires : 1-2(+), 3-6(-) • Can be mounted in a Rack cabinet
LED diodes:	Power, Link/Act, PoE, 17 Uplink, 18 Uplink
Certificates:	CE
Housing:	Metal, Desktop
Power supply:	100 ... 240 V AC
Operation temp:	0 °C ... 40 °C
Weight:	1.6 kg
Dimensions:	285 x 180 x 44 mm
Manufacturer / Brand:	BCS BASIC
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



- 1. LAN + PoE
 - 2. RJ45 (Uplink)
 - 3. SFP (Uplink)
- Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------