

Code: CS4226-24ET-375

## SWITCH POE **CS4226-24ET-375** 24-PORT SFP DAHUA

Net: **761.01 EUR** Gross: **761.01 EUR**

Due to reliability and ensuring high quality of transmission, the CS4226-24ET-375 10/100 Mb/s 24-port PoE desktop type switch is perfect solution for expanding home or office network. 24 ports support the Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLink Care application).

Attention! The SFP port requires the SFP module, which is available in our offer.



### SPECIFICATION

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:            | <ul style="list-style-type: none"><li>• 24 x RJ45 10/100 Base-T ( 2 x Hi-PoE (802.3bt) + 22 x PoE (802.3af/at) ),</li><li>• 2 x port Combo: SFP (1000 Base-X) / RJ45 (10/100/1000 Base-T) - Uplink</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Management:           | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| LED diodes:           | Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Transmission speed:   | <ul style="list-style-type: none"><li>• 10 / 100 Mbps : 24 LAN &amp; PoE ports,</li><li>• 10 / 100 / 1000 : 2 RJ45 (Uplink) ports,</li><li>• 1000 : 2 SFP (Uplink) ports</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Maximal output power: | <ul style="list-style-type: none"><li>• 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports</li><li>• 30 W / port PoE 802.3af/at - 3 ... 24 ports</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Maximal total power:  | 375 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| MAC addresses table:  | 8k                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Operation modes:      | <ul style="list-style-type: none"><li>• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Main features:        | <ul style="list-style-type: none"><li>• Switch is managed through the web and the cloud (DoLink Care application)</li><li>• PoE power mode : The device supports 8-pin power supply</li><li>• Intelligent management of Power Supply Unit power's output stage</li><li>• protection against lightning discharges and voltage differences and strokes between devices</li><li>• Watchdog PoE</li><li>• Loop Protection</li><li>• Compliance with the LLDP protocol</li><li>• Port Based VLAN : 32</li><li>• Data Flow Control (802.3x)</li><li>• DHCP client</li><li>• RESET button</li><li>• Can be mounted in a Rack 19" cabinet</li></ul> |
| Certificates:         | CE                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Protections:          | <ul style="list-style-type: none"><li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li><li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li></ul>                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Housing:              | Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Power supply:         | 100 ... 240 V AC @ 47 ... 63 Hz                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Power consumption:    | max. 400 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Operation temp:       | -10 °C ... 55 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Weight:               | 2.56 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Dimensions:           | 440 x 220 x 44 mm, RACK 19", 1U                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Manufacturer / Brand: | DAHUA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Guarantee:

5 years

## PRESENTATION

Front view:



1. LAN + Hi-PoE (802.3bt)
2. LAN + PoE
3. Combo: RJ45/SFP - Uplink

Rear view:



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm

Gross Weight: 0 kg