

Code: NSW2020-16T1GT1GC-POE-IN

SWITCH POE **NSW2020-16T1GT1GC-POE-IN** 16-PORT SFP UNIVIEW

Net: **272.88 EUR** Gross: **272.88 EUR**

Due to the reliability and ensuring high quality of transmission, the NSW2020-16T1GT1GC-POE-IN 16-port PoE switch is an ideal solution for applications in CCTV IP installations. 16 ports support Power over Ethernet (PoE) function.



SPECIFICATION

LAN ports:	• 16 x RJ45 (16 x PoE (802.3af/at)), • 1 x RJ45 - Uplink, • 1 x Combo: RJ45/SFP - Uplink
Management:	—
LED diodes:	G1/SFP1, G2, PoE Max, Power, Link/Act, PoE
Transmission speed:	• 100 Mbps : 16 LAN & PoE ports, • 1000 Mbps : 2 LAN ports - Uplink, • 1000 Mbps : 1 Port SFP - Uplink
Maximal output power:	30 W / port PoE 802.3af/at
Maximal total power:	225 W
MAC addresses table:	16k
Operation modes:	• Default : 100 m, 100 Mbps • Extend : 250 m, 10 Mbps • VLAN - 1 ... 16 ports are isolated from each other and separately work with the G1, G2 ports
Main features:	• High priority ports : 1 ... 8 • Data Flow Control • Buffer optimization • Power supply PoE - wires : 4-5(+), 7-8(-) • Metal housing • Can be mounted in a Rack 19" cabinet
Certificates:	CE, FCC
Housing:	Desktop, Metal
Power supply:	100 ... 240 V AC, 50 / 60 Hz
Operation temp:	0 °C ... 40 °C
Weight:	2.08 kg
Dimensions:	440 x 195 x 44 mm, RACK 19", 1U
Manufacturer / Brand:	UNIVIEW
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

