

Code: TD-W9970

ACCESS POINT +ROUTER **TD-W9970** 300Mb/s ADSL/VDSL TP-LINK

Net: **38.08 EUR** Gross: **46.84 EUR**

The TD-W9970 router has been designed for sharing Internet connection provided by ADSL Annex A technology. It has built-in ADSL / VDSL modem compatible with ADSL/ADSL2/ADSL2+/VDSL2, Access Point works in IEEE802.11b/g/n standards enabling transmission speed up to 300Mb/s and 4-port switch. The WAN port assembled as RJ11 socket connects directly with telephone line.

The distinctive feature of the device is support for 802.11n standard - capability of using data transfer speeds up to 300Mb/s. The TD-W9970 ensures advanced access control and NAT, its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.



SPECIFICATION

Frequency range:	2.4 ... 2.4835 GHz
Standards:	IEEE 802.11 b/g/n
LAN ports:	4x RJ-45 (10/100 Mbps, Auto MDI/MDX)
WAN interface:	1x RJ-11 ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2
Transmitter power:	< 20 dBm
Baud rates:	<ul style="list-style-type: none">• 300 Mbps - Wi-Fi• 100 Mbps - LAN
Operation modes:	Access Point
Standards:	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite) ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.996.1, ITU-T G.997.1, ITU-T K.2.1 ITU-T G.992.3 (G.dmt.bis), ITU-T G.992.4 (G.lite.bis) ITU-T G.992.5 ITU-T G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP)
DHCP server:	<input type="checkbox"/>
Port USB:	<ul style="list-style-type: none">• Sharing drives or printers and other devices• Local access to data or via FTP server
Firmware update:	<input type="checkbox"/>
DDNS:	<input type="checkbox"/>
Protections:	<ul style="list-style-type: none">• LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL• WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Management interface:	Web browser
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	max. 90 %
Power supply:	12 V DC / 1 A (power adapter included)
Dimensions:	195 x 133 x 36 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:



In the kit:

