

Code: TL-AP200

ACCESS POINT **TL-AP200** 2.4 GHz, 5 GHz 300 Mbps + 433 Mbps TP-LINK

Net: **40.78 EUR** Gross: **40.78 EUR**

The TL-AP200 Access Point operates in 802.11 n/b/g standards, providing many functions and modes of work: AP, AP Client, Repeater, Bridge (Point to Point, Point to Multipoint). Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2 x Omnidirectional antenna
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/ac @ 5 GHz
Baud rates:	300 Mbps + 433 Mbps
Ethernet interface:	1 x 10/100/1000 Mbps
LED indicators:	Power, 2.4 GHz WLAN, 5 GHz WLAN, Ethernet, WAN, WPS
Receiver sensitivity:	2.4 GHz : • 11g 54M : -76 dBm • 11n HT20 MCS7 : -73.5 dBm • 11n HT40 MCS7 : -71 dBm 5 GHz : • 11a 6M : -93 dBm • 11a 54M : -75 dBm • 11ac HT20 : -67 dBm • 11ac HT40 : -62.5 dBm • 11ac HT80 : -59.5 dBm
Firmware update:	✓
Operation mode:	Access Point, Access Point client, Bridge, Multi-SSID
Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK
Management interface:	Web browser
Transmitter power:	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz
Power supply:	12 V DC / 1 A (power adapter included)

Main features:	• Internet access filtering • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • Rate limit • Access control • Remote management
Operation temp. / Relative humidity:	0 °C ... 40 °C / 10 % ... 90 % (non-condensing)
Weight:	0.39 kg
Dimensions:	242 x 165 x 46 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Device connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

