

Code: TL-RE200

# UNIVERSAL WI-FI RANGE EXTENDER **TL-RE200** 2.4 GHz, 5 GHz TP-LINK

Net: **28.25 USD** Gross: **34.75 USD**

The TL-RE200 device greatly extends existing wireless coverage in difficult-to-wire and "dead zones" places. Small dimensions and possibility to connect to the mains socket allow to easy install the device at destination place.  
Easily extends your wireless network at a push of the Range Extender button. Ethernet port allows the device to function as a wireless adapter and connect wired devices via Ethernet cable.



## SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	3 x Antenna Indoor
Standards:	IEEE 802.11 b/g/n/ac
Baud rates:	<ul style="list-style-type: none"><li>• 300 Mb/s @ 2.4 GHz</li><li>• 433 Mb/s @ 5 GHz</li></ul>
Receiver sensitivity:	<p>2.4 GHz :</p> <ul style="list-style-type: none"><li>• 270 Mbps : -70dBm@10% PER</li><li>• 130 Mbps : -70dBm@10% PER</li><li>• 108 Mbps : -73dBm@10% PER</li><li>• 54 Mbps : -75dBm@10% PER</li><li>• 11 Mbps : -86dBm@8% PER</li><li>• 6 Mbps : -92dBm@10% PER</li><li>• 1 Mbps : -94dBm@8% PER</li></ul> <p>5 GHz :</p> <ul style="list-style-type: none"><li>• 390 Mbps : -60dBm@10% PER</li><li>• 180 Mbps : -64dBm@10% PER</li><li>• 78 Mbps : -68dBm@10% PER</li><li>• 54 Mbps : -75dBm@10% PER</li><li>• 29.3 Mbps : -83dBm@10% PER</li><li>• 13.5 Mbps : -87dBm@10% PER</li><li>• 6.5 Mbps : -90dBm@10% PER</li></ul>
LED indicators:	5 GHz, 2.4 GHz, WLAN, LAN, Power, Signal indicator
QSS:	—
Operation mode:	Range Extender - signal amplifier
Protections:	64/128/152-bit WEP, WPA-PSK/WPA2-PSK
Number of LAN ports:	1 x 10/100Mb

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Management interface:	Web browser
Transmitter power:	< 20 dBm (EIRP)
Main features:	<ul style="list-style-type: none"> <li>• WMM (Wi-Fi Multimedia)</li> <li>• MAC addresses filtering</li> <li>• Wireless transmission statistics</li> <li>• Domain Login Function</li> <li>• Access control</li> </ul>
Power supply PoE:	—
Power supply:	230 V AC
Power consumption:	~ 6.5 W
Operation temp. / Relative humidity:	0 °C ... 40 °C / 10 % ... 90 %
Weight:	0.1 kg
Dimensions:	110 x 75 x 66 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

## PRESENTATION

Front panel (LED indicators):



Bottom view:



Rear view:

