

Code: TL-EAP225

ACCESS POINT **TL-EAP225** TP-LINK

Net: **321.73 PLN** Gross: **395.73 PLN**

The TP-Link TL-EAP225 is a device working in MU-MIMO (Multi-User Multiple Input Multiple Output) standard. The MU-MIMO technology allows to optimize data transfer by using multiple transmitters in parallel to connect to several clients simultaneously, taking into account the use of radio wave forming technology (Beamforming - TxBF).

The device is easy to use and manage.



SPECIFICATION

Frequency range:	<ul style="list-style-type: none">• 5150 MHz ... 5875 MHz,• 2412 MHz ... 2462 MHz
Antenna type:	3 x Omnidirectional antenna , Integrated - MIMO : <ul style="list-style-type: none">• 2.4 GHz - 3 x 4 dBi,• 5.0 GHz - 2 x 5 dBi
Standards:	<ul style="list-style-type: none">• IEEE 802.11ac,• IEEE 802.11n,• IEEE 802.11b,• IEEE 802.11g,• IEEE 802.11a
Baud rates:	<ul style="list-style-type: none">• 867 Mbps @ 5 GHz,• 450 Mbps @ 2.4 GHz
Protections:	WEP / WPA / WPA2-Personal / WPA2-Enterprise
LAN ports:	1 x 10/100/1000 Mbps
Operating system:	Omada
Transmitter power:	<ul style="list-style-type: none">• 20 dBm @ 2.4 GHz (max)• 23 dBm @ 5.0 GHz (max)
Power supply PoE:	✓
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 24 V / 0.5 A - PoE Adapter, included
Power consumption:	12.6 W

Main features:	<ul style="list-style-type: none"> • Possibility to mount on the wall or ceiling • Multi-SSID - max. 16 • Transmit power control • Easy and uniform management system for many devices • Intuitive installation and configuration of many advanced functions • AP placement and RF maps • Wireless transmission statistics • Load balance • Rate limit • Airtime Fairness - technology that improves network performance when multiple clients with different data rates appear in it • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • Wireless Network Schedule • Reboot schedule
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 %
Weight:	<ul style="list-style-type: none"> • 0.36 kg • 0.45 kg (with mounting kits)
Dimensions:	205 x 182 x 37 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

PRESENTATION

Top view:



Mounting side view:



Ethernet socket view:



PoE Power Supply and Adapter:



In the kit:



OUR OPINIONS



- Modern and ergonomic design.

