

Code: DS-3WF01C-2N

ACCESS POINT + Customer Premises Equipment **DS-3WF01C-2N** HIKVISION

Net: **191.93 USD** Gross: **236.07 USD**

The DS-3WF01C-2N set of devices allows for quick and convenient configuration of the wireless bridge between two LAN networks, e.g. in separate buildings. The set includes an access point and a client station.

The devices work in 802.11 b/g/n standard, and in addition they are equipped with 2x2 MIMO efficient antennas.

Each of the devices is additionally equipped with 2 LAN ports, one of which enables the powering of the device and a connection to the LAN network, while the other allows to provide network access to another device without using additional switches.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions.



SPECIFICATION

Frequency range:	2412 MHz ... 2472 MHz
Antenna type:	2Tx 2Rx MIMO 6 dBi Integrated
Standards:	• IEEE 802.11 b/g/n
Ethernet interface:	3 x 10/100 Mbps BASE-TX (Cat. 5, RJ-45)
Receiver sensitivity:	• -72 dBm @ 65 Mbps • -97 dBm @ 1 Mbps
Operation mode:	Access Point, Access Point Client, Access Point WDS, WDS client
Transmitter power:	27 dBm
H/V beam width:	65 ° / 60 °
Main features:	Operates in configuration Point-to-Point and Point-to-Multipoint
Power supply PoE:	✓
Power supply:	12 V / 1 A (power adapter included)
Operation temp. / Relative humidity:	-30 °C ... 65 °C / 5 % ... 95 %
Weight:	0.23 kg - Transmitter / Receiver
Dimensions:	150 x 150 x 44 mm - Transmitter / Receiver
Manufacturer / Brand:	HIKVISION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

SAP Code:	301801029
Guarantee:	3 years

PRESENTATION

Front view:



Connectors:



Mounting side view:



In the kit:

