

Code: SXTSQ-5ACD

CUSTOMER PREMISES EQUIPMENT **SXTSQ-5ACD** MIKROTIK

Net: **78.02 EUR** Gross: **78.02 EUR**

The SXTSQ-5ACD is an integrated solution for professional outdoor wireless networks. Thanks to a unique construction, device offers unparalleled performance in such a compact device.

The casing made of UV resistant plastic is resistant to even the most severe weather conditions. The device is compatible with MikroTik RouterOS platform.



SPECIFICATION

Frequency range:	5150 MHz ... 5875 MHz
Antenna type:	16 dBi, 2Tx 2Rx MIMO - Bandwidth 5 GHz
Standards:	IEEE 802.11 a/n/ac
Baud rates:	1000 Mbps
LAN ports:	1 x 10/100/1000 Mbps
Vertical beam width (V):	23 °
Horizontal beam width (H):	23 °
Operation modes:	Client, WDS client, Router, Bridge (Point-to-Point) - 3 The level of license MikroTik RouterOS
Protections:	Overvoltage protection
Transmitter power:	25 dBm
Memory:	256 MB RAM, 16 MB Flash
Processor:	IPQ-4018 4 x 716 MHz
Power supply PoE:	✓
Power supply:	10 V ... 30 V DC PoE (power adapter included)
Power consumption:	7 W
Operation temp:	-40 °C ... 70 °C
Weight:	0.21 kg



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	129 x 129 x 34 mm
Manufacturer / Brand:	MikroTik
Guarantee:	2 years

PRESENTATION

Rear view:



Connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------