

Code: ARCHER-C6

ROUTER ARCHER-C6 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK

Net: 38.32 EUR Gross: 47.13 EUR

With 867 Mbps wireless speeds over the crystal clear 5 GHz band and 300 Mbps over the 2.4 GHz band, ARCHER-C6 offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. 4 external antennas provide stable omnidirectional signal and superior wireless coverage.

Supports 802.11ac standard - the next generation of Wi-Fi.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	<ul style="list-style-type: none">• 4 x Omnidirectional antenna - Outdoor,• 1 x Internal antenna
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	300 Mbps + 867 Mbps
LAN ports:	4 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps Uplink
LED indicators:	Power, 2.4 GHz WLAN, 5 GHz WLAN, 4 x Ethernet, WAN, WPS
Receiver sensitivity:	2.4 GHz : <ul style="list-style-type: none">• 11g 54M : -78 dBm• 11n HT20 : -74 dBm• 11n HT40 : -71 dBm 5 GHz : <ul style="list-style-type: none">• 11a 6M : -93 dBm• 11a 54M : -78 dBm• 11ac HT20 : -69 dBm• 11ac HT40 : -65 dBm• 11ac HT80 : -62 dBm
DDNS:	✓
DHCP server:	✓
Firmware update:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Protections:	WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface:	Web browser, TP-LINK Tether
Transmitter power:	max. 20 dBm @ 2.4 GHz max. 23 dBm @ 5 GHz
Power supply:	12 V DC / 1 A (power adapter included)
Main features:	<ul style="list-style-type: none"> • TP-Link OneMesh™ support • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests • SSID hiding
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.35 kg
Dimensions:	257 x 161 x 215 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

PRESENTATION



Device connectors:



In the kit:

