

Code: TL-WA801ND

## ACCESS POINT **TL-WA801ND** TP-LINK

Net: **22.72 EUR** Gross: **27.95 EUR**

The TP-Link TL-WA801ND is a device working in MU-MIMO (Multi-User Multiple Input Multiple Output) standard. The MU-MIMO technology allows to optimize data transfer by using multiple transmitters in parallel to connect to several clients simultaneously.

The device is easy to use and manage.



### SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	2 x Omnidirectional antenna (złącze SMA R/P) - 2 x 2 MIMO, 2 x 5 dBi
Standards:	<ul style="list-style-type: none"><li>• IEEE 802.11n,</li><li>• IEEE 802.11g,</li><li>• IEEE 802.11b</li></ul>
Baud rates:	300 Mbps
Protections:	WEP / WPA / WPA2-Personal / WPA2-Enterprise
LAN ports:	1 x 10/100 Mbps
Transmitter power:	20 dBm (max)
Receiver sensitivity:	270M : -68 dBm @ 10 % PER 130M : -68 dBm @ 10 % PER 108M : -68 dBm @ 10 % PER 54M : -68 dBm @ 10 % PER 11M : -85 dBm @ 8 % PER 6M : -88 dBm @ 10 % PER 1M : -90 dBm @ 8 % PER
Operation modes:	Access Point, Access Point Client, Repeater, Bridge (Point to Point, Point to Multipoint)+AP
Power supply PoE:	✓
Power supply:	9 V / 0.6 A - Power adapter + PoE Adapter included
Power consumption:	5.8 W

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> <li>• Possibility to mount on the wall or ceiling</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• Multi-SSID</li> <li>• Remote management</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Wireless transmission statistics</li> <li>• Rate limit</li> </ul>
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 %
Weight:	0.19 kg
Dimensions:	180 x 126 x 35 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

## PRESENTATION

Front view:



Rear panel:



In the kit:



## OUR OPINIONS



- Modern and ergonomic design.