

Code: TL-RE305

UNIVERSAL WI-FI RANGE EXTENDER **TL-RE305** 2.4 GHz, 5 GHz TP-LINK

Net: **41.91 EUR** Gross: **41.91 EUR**

The TL-RE305 device greatly extends existing wireless coverage in difficult-to-wire and "dead zones" places.

Thanks to the advanced OneMesh technology, devices are automatically switched when moving around the house. In addition, the device can also work as a wireless access point, increasing the functionality of the existing wired network by Wi-Fi connection.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	2 x Omnidirectional antenna - Outdoor
Standards:	IEEE 802.11 a/b/g/n/ac
Baud rates:	• 300 Mbps @ 2.4 GHz • 867 Mbps @ 5 GHz
Receiver sensitivity:	2.4 GHz : • 54 Mbps 11g : -79 dBm @ 10% PER • HT20 mcs7 11n : -77 dBm @ 10% PER • HT40 mcs7 11n : -74 dBm @ 10% PER 5 GHz : • 6 Mbps 11a : -91 dBm @ 10% PER • 54 Mbps 11a : -74 dBm @ 10% PER • HT20 mcs8 11ac : -68 dBm @ 10% PER • HT40 mcs9 Mbps 11ac : -63 dBm @ 10% PER • HT80 mcs9 Mbps 11ac : -59 dBm @ 10% PER
LED indicators:	5 GHz, 2.4 GHz, Power, Wi-Fi - Signal indicator
QSS:	—
Operation modes:	• Range Extender - signal amplifier • Access Point - Access Point mode
Protections:	64/128-bit WEP, WPA/WPA-PSK2
LAN ports:	1 x (RJ45) 10/100 Mb - Ethernet
Management interface:	Web browser, Tether application

Transmitter power:	< 17 dBm @ 2.4 GHz < 17 dBm @ 5 GHz
Main features:	• Support for TP-Link OneMesh™ technology • 2.4 GHz (300Mb/s) and 5 GHz (867Mb/s) bands support • Intelligent LED indicator helps you find the best location for the device, which can achieve optimal network coverage • Wireless transmission statistics • Access control • Domain Login Function • Access Point - Built-in • WPS button • RESET button
Power supply PoE:	—
Power supply:	230 V AC
Power consumption:	≤ 7.3 W
Operation temp:	0 °C ... 30 °C
Permissible relative humidity:	10 % ... 90 %
Weight:	0.15 kg
Dimensions:	80 x 78 x 77 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION



Top view:



Bottom view:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------