

Code: TL-M7000

MODEM 4G LTE, MOBILE ROUTER **TL-M7000** Wi-Fi 300Mb/s TP-LINK

Net: **70.41 EUR** Gross: **70.41 EUR**

Portable LTE hotspot.

The TL-M7000 supports the latest generation of 4G FDD/TDD-LTE connections, ensuring a seamless connection to the Internet in most countries and regions. The device allows you to easily share the network connection up to 10 devices simultaneously.



SPECIFICATION

Frequency range:	2.4 GHz
Antenna type:	1 x WiFi - Internal antenna , 1 x 4G LTE - Internal antenna
Standards:	IEEE 802.11 b/g/n, 4G LTE, 3G HSPA+/HSPA/UMTS
Baud rates:	• LTE : 150 / 50 Mbps, • 11n : 300 Mbps, • 11g : 54 Mbps, • 11b : 11 Mbps
Network type:	• 4G : FDD-LTE B1/B3/B5/B7/B8/B20 - 2100 / 1800 / 850 / 2600 / 900 / 800 MHz • 4G : TDD-LTE B38/B40/B41 - 2600 / 2300 / 2500 MHz • 3G : HSPA+/HSPA/UMTS B1/B5/B8 - 2100 / 850 / 900 MHz
LAN ports:	—
Ports:	• 1 x micro USB - Battery charging • 1 x SIM socket
Receiver sensitivity:	• 11b 11 Mbps : -87.5 dBm • 11g 54 Mbps : -74 dBm • 11n HT20 MCS7 : -70 dBm • 11n HT40 MCS7 : -68 dBm
Transmitter power:	< 20 dBm

Main features:	• ON/OFF button • RESET button • LED diodes : WiFi, INTERNET, Battery • Transmission encryption : WPA-PSK/WPA2-PSK • MAC addresses filtering • SSID hiding • DHCP server • DHCP client list • Max. number of supported devices : 10 • Backup time max. 8 h • Remote management - tpMiFi application • System requirements : Windows XP/Vista/7/8/10, Mac OS, Android, iOS (iPhone, iPad), Windows Phone
Power supply:	• 2000 mAh Battery • 5 V DC / 1 A Charging via USB port
Operation temp:	0 °C ... 35 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.09 kg
Dimensions:	94 x 57 x 20 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

PRESENTATION



micro USB connector:



Internal view of the housing:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------