

Code: TL-MR3420

ACCESS POINT UMTS/HSPA+ROUTER **TL-MR3420** 300Mb/s TP-LINK

Net: 120.34 PLN Gross: 148.02 PLN

The TL-MR3420 3G/4G Wireless Router, operating in accordance with the N standard, allows to share a network connection between several users in areas that are covered by 3G signal. To establish a network connection with Wi-Fi hotspot, you should connect the USB 3G/4G modem to the router.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	2 x 3 dBi
Standards:	802.11n/g/b IEEE 802.3/3u USB 2.0
Baud rates:	11n : 300 Mb/s 11g : 54 Mb/s 11b : 11 Mb/s
Modulation type:	DBPSK, DQPSK, CCK OFDM, 16-QAM, 64-QAM
LAN ports:	1 x 10/100 Mbps - LAN/WAN 4 x 10/100 Mbps - LAN
Receiver sensitivity:	<ul style="list-style-type: none">• 270M: -68dBm@10% PER• 130M: -68dBm @ 10% PER• 108M: -68dBm @ 10% PER• 54M: -68dBm @ 10% PER• 11M: -85dBm @ 8% PER• 6M: -88dBm @ 10% PER• 1M: -90dBm @ 8% PER
LTE:	✓
QSS:	✓
WDS:	✓
Management interface:	USB 2.0 for UMTS/HSPA/EVDO modems
Transmitter power:	max. 20 dBm
Power supply:	12 V DC / 0.85 A (power adapter included)
Operation temp:	0 °C ... 40 °C

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Permissible relative humidity:	max. 95 % (non-condensing)
Main features:	<ul style="list-style-type: none"> • The failover function enabling automatic switching between 3G/WAN interface in the case of an Internet network connection loss • IP-layer bandwidth control mechanism • Compatible with modems: LTE/HSPA+/HSUPA/HSDPA/UMTS/EVDO USB
Weight:	0.250 kg
Dimensions:	174 x 162 x 35 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:



Side view:



In the kit:

