

Code: TL-WR802N

ROUTER **TL-WR802N** 300 Mbps TP-LINK

Net: **23.14 EUR** Gross: **28.46 EUR**

The TL-WR802N mini-size router is ideal for home and travel use. Simple and easy installation and operation.

Due to 5 operation modes, the TL-WR802N is an extremely versatile device.

The TL-WR802N ensures advanced access control and QoS, its DHCP server supports static assignment of IP addresses.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	Indoor
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
Modulation type:	OFDM, BPSK, QPSK
LAN ports:	1 x 10/100 Mbps (RJ-45)
LED indicators:	Power, Connection status
Receiver sensitivity:	<ul style="list-style-type: none">• 270M: -65dBm@10% PER• 130M: -70dBm@10% PER• 108M: -82dBm@10% PER• 54M: -73dBm@10% PER• 11M: -82dBm@8% PER• 6M: -86dBm@10% PER• 1M: -90dBm@8% PER
DDNS:	<ul style="list-style-type: none">• No-IP• DynDNS• Comexe
DHCP server:	✓
Firmware update:	✓
Operation modes:	<ul style="list-style-type: none">• Router,• AP,• Client,• Repeater,• Bridge
Protections:	64/128/152-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Table of access / access-deny according to MAC addresses of client cards Internet access filtering via filters of IP addresses, MAC addresses and ports of TCP/IP protocol
Management interface:	Web browser

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Transmitter power:	< 20 dBm
Power supply:	<ul style="list-style-type: none"> • 5 V DC / 600 mA (power adapter included) • from USB port
Main features:	<ul style="list-style-type: none"> • MAC address cloning • Firewall • Internet access filtering • Static / dynamic routing
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	90 % (non-condensing)
Weight:	0.170 kg
Dimensions:	57 x 57 x 18 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

The device is tiny sizes:



Connectors:



Top view:



In the kit:

