

Code: ARCHER-T4U-PLUS

WLAN USB ADAPTER **ARCHER-T4U-PLUS** 400 Mbps @ 2.4 GHz, 867 Mbps @ 5 GHz TP-LINK

Net: 29.44 EUR Gross: 29.44 EUR

Wireless card is practical wireless adapter for use in WiFi networks. The adapter/card is connected to USB port, so it is well suited for portable computers.

Enhanced encryption capabilities allow to protect the connections against unauthorized access.

Supports 802.11ac standard - the next generation of Wi-Fi.

Configuration of the card is very easy. The included software enables the user to monitor operation and transmission parameters. It can also operate in roaming between Access Points in Infrastructure mode.



SPECIFICATION

Supported standards:	IEEE 802.11 b/g/n @ 2.4 GHz, IEEE 802.11 a/n/ac @ 5 GHz
Supported transmission speeds:	400 Mbps @ 2.4 GHz , 867 Mbps @ 5 GHz
Operation modes:	Infrastructure
Antenna type:	2 x Omnidirectional antenna 5 dBi - Outdoor, Integrated
Interface:	USB 3.0
Frequency range:	• 2.4 GHz • 5 GHz
Transmitter power:	• 18 dBm @ 2.4 GHz, • 20 dBm @ 5 GHz
Receiver sensitivity:	5 GHz • 11a 54M : -77 dBm • 11n HT20 : -74 dBm • 11n HT40 : -71 dBm • 11ac VHT20 : -69 dBm • 11ac VHT40 : -65 dBm • 11ac VHT80 : -62 dBm 2.4 GHz • 11b 11M : -87 dBm • 11g 54M : -75 dBm • 11n HT20 : -72 dBm • 11n HT40 : -70 dBm
Security measures:	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

Main features:	• STATUS indicator • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network
Included drivers:	Windows 7 / 8 / 8.1 / 10 / 11, Mac OS < 10.15
Certificates:	CE, FCC, RoHS
Operation temp:	0 °C ... 40 °C
Weight:	0.06 kg
Dimensions:	• 156 x 84 x 19 mm • Length of the cable : 100 cm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION



Connectors:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

