

Code: HAC-HFW1230D-0360B

AHD, HD-CVI, HD-TVI, PAL CAMERA **HAC-HFW1230D-0360B** - 1080p 3.6 mm DAHUA

Net: **69.87 EUR** Gross: **85.94 EUR**

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.

Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately.

The "Starlight" series cameras provide a clear color image even at very poor lighting.



SPECIFICATION

Standard:	HD-CVI, HD-TVI, AHD, PAL
Matrix size:	2.1 Mpx
Sensor:	1/2.8 " Progressive Scan CMOS
Resolution:	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Video output:	HD-CVI / HD-TVI / AHD / PAL - 1 Vpp / 75 Ω
Lens:	3.6 mm
View angle:	• 87 ° (manufacturer data) • 84 ° (our tests result)
S/N ratio:	> 65 dB
Range of IR illumination:	80 m
IR illuminator power adjustment:	Automatic
Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 2D-DNR - Digital Noise Reduction• BLC/HLC - Back Light / High Light Compensation• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect• ICR - Movable InfraRed filter• AGC - Automatic Gain Control• Auto White Balance• Mirror - Mirror image• Configurable Privacy Zones• Sharpness - sharper image outlines
OSD menu:	OSD menu available via recorder
Power supply:	12 V DC / 460 mA
Power consumption:	≤ 5.6 W

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Housing:	Compact, Metal
Color:	White
"Index of Protection":	IP67
Operation temp:	-40 °C ... 60 °C
Weight:	0.6 kg
Dimensions:	242 x 90 x 90 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION


Front view:




Side view:



Mounting side view:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions with internal built-in IR illuminator on:



HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- The "Starlight" series cameras provide a clear color image even at very poor lighting.