

Code: DH-HAC-HUM1220AP-W-0

AHD, HD-CVI, HD-TVI, PAL HIDDEN CAMERA **DH-HAC-HUM1220AP-W-0**
280B-PIR - 1080p 2.8 mm DAHUA
Net: **88.24 EUR** Gross: **88.24 EUR**

Megapixel camera with 1/2.9" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.
The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in 1080p resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.
Setting the camera in PAL mode allows to obtain an image in 960H resolution.
Attention! The camera default setting is HD-CVI standard. To change the camera standard you need use the PFM820 controller, available separately.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/2.9 " CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p, AHD-H, HD-CVI, HD-TVI , 960 x 576 - 960H PAL
Lens:	2.8 mm
View angle:	• 101 ° (manufacturer data) • 97 ° (our tests result)
S/N ratio:	> 65 dB
Video output:	1 Vpp 75 Ω, AHD, HD-CVI, HD-TVI, PAL
PIR DETECTOR:	✓
Pyroelectric sensor:	Double
Sensor type:	Passive Infra Red (PIR)
Detection angle / Detection range:	100 ° / 12 m
Recommended installation height:	2.2 ... 2.5 m
Frequency range:	433 MHz
Radio communication range (at open area):	max. 1000 m
Pet immunity:	≤ 18 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Sensitivity adjustment:	2 - step
Main features:	• Sense-UP - increase the camera sensitivity x30 • F-DNR (Defog) - Reduction of image noise caused by precipitation • WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Mirror - Mirror image • Privacy zones - max. 4 • Motion Detection • Sharpness - sharper image outlines • Auto White Balance
OSD menu:	OSD menu available via DAHUA recorder
Application:	The camera is designed for indoor use, due to the possibility of steam condensation.
Power supply:	12 V DC / 60 mA
Housing:	Spy, Plastic
Color:	White
Operation temp:	-10 °C ... 50 °C
Weight:	0.13 kg
Dimensions:	120 x 62 x 59 mm
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION



Front view:



Internal view:



Mounting side view:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

10 LUX:




1 LUX:



0.1 LUX:



0.01 LUX:



HD-CVI:

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

10 LUX:



1 LUX:



0.1 LUX:



0.01 LUX:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at direct strong light opposite to camera:



Camera image at night conditions, at different illumination values show below:

10 LUX:



1 LUX:



0.1 LUX:



0.01 LUX:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------