

Code: DS-7204HUHI-K1

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DS-7204HUHI-K1** 4 CHANNELS

Hikvision

Net: **216.72 USD** Gross: **266.57 USD**

The DS-7204HUHI-K1 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / PAL
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.265+ / H.264 / H.264+
Image records resolutions:	<ul style="list-style-type: none">• HD-TVI : 5.0 Mpx - 2560 x 1944, 3.7 Mpx - 2560 x 1440, 3 Mpx - 1920 x 1536, 1080p - 1920 x 1080, 720p - 1280 x 720,• AHD : 5.0 Mpx - 2560 x 1944, 3.7 Mpx - 2560 x 1440, 1080p - 1920 x 1080, 720p - 1280 x 720,• HD-CVI : 3.7 Mpx - 2560 x 1440, 1080p - 1920 x 1080, 720p - 1280 x 720,• PAL : 960H - 960 x 576,• IP : max. 8.0 Mpx - 3840 x 2160
Recording speed adjustment:	<ul style="list-style-type: none">1 ... 25 fps @ 3840 x 2160 px IP1 ... 12 fps @ 2560 x 1944 px1 ... 15 fps @ 2560 x 1440 px1 ... 18 fps @ 1920 x 1536 px1 ... 25 fps @ 1920 x 1080 px1 ... 25 fps @ 1280 x 720 px1 ... 25 fps @ 704 x 5761 ... 25 fps @ 640 x 480 px for each channel
Operation modes:	Firmware V3.5.37 build 180801 4 x HD-TVI / AHD / HD-CVI / PAL / IP + 2 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 10 TB SATA
External storage devices backup:	Backup to USB drive (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network interface:	1 x RJ-45 - 10/100 Base-TX

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Bitrate:	32 ... 10240 kbps
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500
Default IP address:	DHCP or 192.168.1.64
Default admin user / password:	admin / -
Web browser access ports:	80
PC client access ports:	554 RTSP, 8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	4 / 1
PTZ control:	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Main features:	Intelligent Image Analysis : intrusion, crossing the line (tripwire)
Power supply:	12 V DC / 1.5 A (power adapter included)
Color:	Black
Weight:	1.2 kg
Dimensions:	315 x 250 x 47 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300219673
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



In the kit:

