

Code: HYBRO-H04A1-S2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **HYBRO-H04A1-S2** 4 CHANNELS

Net: **232.00 PLN** Gross: **285.36 PLN**

The HYBRO-H04A1-S2 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	<ul style="list-style-type: none">• AHD / HD-CVI / HD-TVI : 1920 x 1080, 960 x 1080, 1280 x 720• AHD-L / PAL : 928 x 576• PAL : 704 x 576• IP : 2592 x 1944, 1920 x 1080, 1280 x 960
Maximal total frame rate:	<ul style="list-style-type: none">• AHD / HD-CVI / HD-TVI : 60 fps @ 1920 x 1080 px, 100 fps @ 960 x 1080 px, 100 fps @ 1280 x 720 px,• AHD / PAL : 100 fps @ 928 x 576 px, 100 fps @ 704 x 576 px,• IP : 400 fps @ 1920 x 1080 px 100 fps @ 2952 x 1944 px
Recording speed adjustment:	<ul style="list-style-type: none">1 ... 15 fps @ 1920 x 10801 ... 25 fps @ 960 x 1080 px1 ... 25 fps @ 1280 x 720 px1 ... 25 fps @ 928 x 576 px1 ... 25 fps @ 704 x 576 for each channel
Operation modes:	<ul style="list-style-type: none">• 4 x AHD / HD-CVI / HD-TVI @ 1080p• 4 x AHD / HD-CVI / HD-TVI @ 1080N• 2 x AHD / HD-CVI / HD-TVI @ 1080p + 2 x IP @ 1080p• 4 x AHD / HD-CVI / HD-TVI @ 1080N + 4 x IP 960p• 4 x IP max. 5 Mpx• 16 x IP max. 1080p All modes allow for any combination of the AHD-H, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 10 TB SATA
External storage devices backup:	Records backup at (.avi) / (.h264) format to USB (pendrive)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions:	Network Client software or IE browser: playback, DVR settings, files download, records searching
Mobile phones support:	Port no.: 34567 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Darmowa aplikacja XMEye • iOS (iPhone): Darmowa aplikacja XMEye
Alarm inputs / outputs:	<input checked="" type="checkbox"/>
PTZ control:	RS-485 - PELCO-D/P and others
Motion Detection:	Split the screen into zones : 16 x 12 motion zones
Mouse support:	<input checked="" type="checkbox"/>
IR remote controller in the set:	<input checked="" type="checkbox"/>
Power supply:	12 V DC / 3 A (power adapter included)
Color:	Black
Weight:	0.80 kg
Dimensions:	255 x 225 x 44 mm
Supported languages:	English, Arabic, Brazilian Portuguese, Bulgarian, Chinese Traditional, Chinese Simplified, Czech, Finnish, French, Greek, Hebrew, Spanish, Dutch, Indonesian (Bahasa), Japanese, German, Persian, Polish, Portuguese, Russian, Romanian, Slovenian, Swedish, Thai, Turkish, Hungarian, Vietnamese, Italian
Country of origin:	China
Manufacturer / Brand:	HYBRO
Guarantee:	2 years

PRESENTATION

Top view:



Rear view:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

OUR OPINIONS



- Small dimensions of the device.

