

Code: APTI-NX0401-S32

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-NX0401-S32** 4 CHANNELS

Net: **46.55 USD** Gross: **57.26 USD**

The APTI-NX0401-S32 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

| | |
|-------------------------------------|--|
| Standard: | AHD, HD-CVI, HD-TVI, PAL, TCP/IP |
| Video inputs: | 4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS |
| Video outputs: | 1 pcs HDMI 1 pcs VGA |
| Audio inputs: | 4 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.264 |
| Image records resolutions: | <ul style="list-style-type: none">• AHD / HD-CVI / HD-TVI : 960 x 1080, 1280 x 720• AHD / PAL : 960 x 576,• IP : max. 1920 x 1080 |
| Recording speed adjustment: | <ul style="list-style-type: none">1 ... 25 fps @ 1920 x 1080 px - IP1 ... 25 fps @ 960 x 1080 px1 ... 25 fps @ 1280 x 720 px1 ... 25 fps @ 960 x 576 px for each channel! |
| Operation modes: | <ul style="list-style-type: none">• 4 x AHD / HD-CVI / HD-TVI @ 1080N• 2 x AHD / HD-CVI / HD-TVI @ 1080N + 2 x IP @ 1080p• 9 x IP max. 1080p All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras |
| Recording modes: | Motion Detection, Schedule |
| Supported hard drives: | 1 x 8 TB SATA |
| External storage devices backup: | Records backup at (.avi) format to USB (pendrive) |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time |
| Network functions: | Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters |
| Mobile phones support: | Port no.: 554 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application FREEIP PRO, Android: Free application FREEIP• iOS (iPhone): Free application FREEIP PRO, iOS (iPhone): Free application FREEIP |
| Default IP address: | 192.168.1.88 |
| Default admin user / password: | admin / 12345 |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|----------------------------------|--|
| Web browser access ports: | 80, 5000, 554 |
| PC client access ports: | 80, 5000, 554 |
| Mobile client access ports: | 80, 5000, 554 |
| Alarm inputs / outputs: | — |
| PTZ control: | Pelco-D, Pelco-P |
| Motion Detection: | Split the screen into zones : 22 x 18 motion zones |
| Mouse support: | ✓ |
| USB: | 2 pcs USB 2.0 |
| IR remote controller in the set: | — |
| Power supply: | 12 V DC / 2 A (power adapter included) |
| Color: | Black |
| Weight: | 0.75 kg |
| Dimensions: | 260 x 225 x 46 mm |
| Supported languages: | Polish, English, Bulgarian, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | APTI |
| Guarantee: | 2 years |

PRESENTATION

Front panel:



Rear view:



In the kit:



Configuration and operation of the FreeIP cloud:

: