

Code: XVR5104H-X-4P

# AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **XVR5104H-X-4P** 4 CHANNELS DAHUA

Net: **166.59 EUR** Gross: **204.91 EUR**

The XVR5104H-X-4P digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

The PoC (Power over Coaxial) technology used in the device allows to power the compatible with this standard cameras via a coaxial cable directly from the recorder, eliminating the need for additional wires or power supplies.



## SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC
Video outputs:	<ul style="list-style-type: none"><li>• 1 pcs HDMI</li><li>• 1 pcs VGA</li></ul>
Audio inputs:	<ul style="list-style-type: none"><li>• 1 pcs CINCH,</li><li>• 4 - Audio support via coaxial cable, HD-CVI only</li></ul>
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Number of compression levels:	6
Image records resolutions:	<ul style="list-style-type: none"><li>• AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1944 , 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720</li><li>• CVBS : 960H - 960 x 576</li><li>• IP : 6 Mpx - 3072 x 2048</li></ul>
Recording speed adjustment:	<ul style="list-style-type: none"><li>6 Mpx IP @ 1 ... 25 fps</li><li>5M-N @ 1 ... 10 fps</li><li>4M-N @ 1 ... 15 fps</li><li>1080p @ 1 ... 15 fps</li><li>1080N @ 1 ... 25 fps</li><li>720p @ 1 ... 25 fps</li><li>960H @ 1 ... 25 fps</li></ul> for each channel
Operation modes:	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 10 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">gDMSS Plus</a> or <a href="#">DMSS</a></li> <li>• iOS (iPhone): Free application <a href="#">iDMSS Plus</a> or <a href="#">DMSS</a></li> </ul> <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>
Alarm inputs / outputs:	—
PTZ control:	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Main features:	<ul style="list-style-type: none"> <li>• The PoC (Power over Coaxial) technology used in the device allows to power the compatible with this standard cameras via a coaxial cable directly from the recorder, eliminating the need for additional wires or power supplies</li> <li>• Intelligent Image Analysis : crossing the line (tripwire), intrusion, abandoned/missing object, face detection</li> </ul>
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	<ul style="list-style-type: none"> <li>• 53 V DC / 1.13 A (power adapter included)</li> <li>• Support for PoC (Power over Coaxial)</li> </ul>
Color:	Black
Weight:	1.16 kg
Dimensions:	325 x 255 x 55 mm
Supported languages:	Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>

## PRESENTATION

Front panel:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

In the kit:



Example captures of device interface:

