

Code: XVR-104G2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **XVR-104G2** 4 CHANNELS UNIARCH

Net: **62.71 EUR** Gross: **77.13 EUR**

The XVR-104G2 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	4 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	<ul style="list-style-type: none">• 1 pcs CINCH,• 4 - Audio support via coaxial cable
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264
Image records resolutions:	<ul style="list-style-type: none">• AHD / HD-TVI : 5M-N - 1296 x 1944 - For cameras 12 fps ,• AHD / HD-CVI / HD-TVI : 5M-N - 1296 x 1944 - For cameras 20 fps 1 CH only , 4M-N - 1280 x 1440 - For cameras 15 fps, 30 fps 1 CH only , 1080p - 1920 x 1080 , 720p - 1280 x 720• CVBS : 960H - 960 x 576 ,• IP : max. 4 Mpx - 2560 x 1440
Recording speed adjustment:	4 Mpx IP @ 1 ... 25 fps , 5M-N @ 1 ... 12 fps , 4M-N @ 1 ... 15 fps , 1080p @ 1 ... 15 fps , 720p @ 1 ... 30 fps , 960H @ 1 ... 30 fps for each channel
Operation modes:	4 x AHD / HD-CVI / HD-TVI / CVBS / IP + 2 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive

Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy) Synchronous playback of all channels
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users
USB:	2 x USB 2.0
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application Uniarch • iOS (iPhone): Free application Uniarch
Alarm inputs / outputs:	—
PTZ control:	PTZ Uniarch cameras
Motion Detection:	✓
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Power consumption:	≤ 8 W (without HDD)
Color:	Black
Weight:	0.84 kg
Dimensions:	255 x 260 x 46 mm
Supported languages:	English, Czech, French, Spanish, Dutch, German, Polish, Portuguese, Slovak, Italian
Manufacturer / Brand:	UNIVIEW / UNIARCH
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



In the kit:

