

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-NX0802-S4 8 CHANNELSNet: **144.17 EUR** Gross: **144.17 EUR**

The APTI-NX0802-S4 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

**SPECIFICATION**

Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	• AHD / HD-TVI : 2592 x 1954, 2048 x 1536, 1920 x 1080, 1296 x 1954, • AHD / HD-CVI : 2560 x 1440, 1920 x 1080, 1280 x 1440, • CVBS : 960 x 576 • IP : max. 3840 x 2160 ,
Maximal total frame rate:	• AHD / HD-TVI : 96 fps @ 2592 x 1954 px, 128 fps @ 2048 x 1536 px, • AHD / HD-CVI : 120 fps @ 2560 x 1440 px • AHD / HD-CVI / HD-TVI : 200 fps @ 1080p, 200 fps @ 720p • IP : 800 fps @ 3840 x 2160 px
Recording speed adjustment:	1 ... 12 fps @ 2592 x 1954 px 1 ... 15 fps @ 2560 x 1440 px 1 ... 18 fps @ 2048 x 1536 px 1 ... 25 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px for each channel
Operation modes:	• 8 x AHD / HD-CVI / HD-TVI / PAL • 6 x AHD / HD-CVI / HD-TVI / PAL + 10 x IP max. 8 Mpx • 4 x AHD / HD-CVI / HD-TVI / PAL + 12 x IP max. 8 Mpx • 2 x AHD HD-CVI HD-TVI PAL + 14 IP max. 8 Mpx • 32 x IP max. 8 Mpx - 200 Mbps (max) All modes allow for any combination of the AHD, HD-CVI, HD-TVI, PAL cameras
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)

Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 8 channels in the same time
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Mobile phones support:	Port no.: 554 or access by a cloud (P2P) • Android: Free application FREEIP PRO , Android: Free application FREEIP • iOS (iPhone): Free application FREEIP PRO , iOS (iPhone): Free application FREEIP
Default IP address:	192.168.1.168
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Alarm inputs / outputs:	—
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.81 kg
Dimensions:	260 x 227 x 45 mm
Supported languages:	English, Bulgarian, Chinese, Czech, Spanish, German, Polish, Portuguese, Russian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



In the kit:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Configuration and operation of the FreeIP cloud:
:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------