

Code: XVR5108HS-X+2TB

PROMOTIONAL SET DVR + HDD **XVR5108HS-X+2TB** 8 CHANNELS DAHUA

Net: **256.15 EUR** Gross: **256.15 EUR**

Promotional set for the XVR5108HS-X recorder with the HDD-ST2000VX003 hard disk.

The XVR5104HS-X digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem. The disk is designed for reliable 24-hour operation in CCTV surveillance systems. Serial ATA interface connection.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	8 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	• 1 pcs - CINCH • 8 - Audio support via coaxial cable, HD-CVI only
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.265+ / H.264 / H.264+
Number of compression levels:	6
Image records resolutions:	• AHD / HD-CVI / HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 • IP : max. 6 Mpx - 3072 x 2048
Recording speed adjustment:	6 Mpx IP @ 1 ... 25 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	8 x AHD / HD-CVI / HD-TVI / CVBS @ 4M-N / IP + 4 x IP
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 10 TB SATA

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Alarm inputs / outputs:	—
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
PTZ control:	IP Speed Dome Cameras Control compatible with coax PTZ HD-CVI RS-485 - PELCO-D/P
Main features:	Intelligent Image Analysis : crossing the line (tripwire), crossing the line (tripwire), abandoned/missing object, face detection
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Supported languages:	Polish, English, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Hungarian, Italian
Weight:	0.91 kg
Dimensions:	260 x 236 x 48 mm
Country of origin:	China
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

HDD FOR DVR:

Capacity:	2 TB
Interface:	Serial ATA/600
Spindle speed:	5900 RPM
Size format:	3.5 "
Cache memory:	64 MB
Average latency:	8 ms
Technology:	• NCQ - Native Command Queuing • AcuTrac - technology provides high reliability and performance of reading/writing in harsh environments
Designed to continuous operation 24/7:	✓
Weight:	0.524 kg
Manufacturer / Brand:	SEAGATE
Guarantee:	2 years

PRESENTATION

DVR:

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60





Rear view:



In the kit:



Example captures of device interface:



HDD FOR DVR:

Top view:



The Seagate SKYHAWK drives marked "surveillance video recording" are designed to work in video surveillance systems. Its design allows for error-free recording of several Full HD streams in 24/7 mode.

Connectors:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------