

Code: APTI-XB0801H-S32

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-XB0801H-S32** 8 CHANNELS

Net: **119.85 EUR** Gross: **147.42 EUR**

The APTI-XB0801H-S32 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

Attention! The APTI-XBxxxx series recorders are supported by the new BitVision and IVMS320 applications. The device does not work with the FREEIP application.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	8 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	<ul style="list-style-type: none">• 1 pcs HDMI• 1 pcs VGA• 1 pcs Composite Video (CVBS) - BNC socket
Audio inputs:	6 pcs CINCH
Audio outputs:	2 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Image records resolutions:	<ul style="list-style-type: none">• AHD / HD-TVI : 8M-N - 1920 x 2160 px, 5 Mpx - 2592 x 1944 px, 5M-N - 1296 x 1944 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px,• HD-CVI : 8M-N - 1920 x 2160 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px,• CVBS : 960H - 960 x 576 px,• IP : max. 8.3 Mpx - 3840 x 2160 px
Recording speed adjustment:	<ul style="list-style-type: none">8.3 Mpx IP @ 1 ... 25 fps8M-N @ 1 ... 8 fps5 Mpx @ 1 ... 6 fps5M-N @ 1 ... 10 fps4 Mpx @ 1 ... 8 fps4M-N @ 1 ... 15 fps3 Mpx @ 1 ... 9 fps1080p @ 1 ... 15 fps720p @ 1 ... 25 fps960H @ 1 ... 25 fpsfor each channel



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation modes:	<ul style="list-style-type: none"> • 8 x AHD / HD-CVI / HD-TVI / CVBS + 4 x IP max. 5 Mpx • 6 x AHD / HD-CVI / HD-TVI / CVBS + 8 x IP max. 8.3 Mpx • 4 x AHD / HD-CVI / HD-TVI / CVBS + 10 x IP max. 8.3 Mpx • 2 x AHD / HD-CVI / HD-TVI / CVBS + 12 x IP max. 8.3 Mpx • 16 x IP max. 8.3 Mpx All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	1 x 8 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions:	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision, Android: Free application iVMS320 • iOS (iPhone): Free application BitVision, iOS: Free application iVMS320
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 6000
Alarm inputs / outputs:	—
PTZ control:	Pelco-D, Pelco-P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.82 kg
Dimensions:	260 x 242 x 45 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Top view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Rear view:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:

