

Code: DS-7216HUHI-K2

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DS-7216HUHI-K2** 16 CHANNELS

Hikvision

Net: **631.32 EUR** Gross: **631.32 EUR**

The DS-7216HUHI-K2 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface) and PAL interface is a professional device applicable in surveillance systems. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, TCP/IP, PAL
Video inputs:	16 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.265+ / H.264 / H.264+
Image records resolutions:	<ul style="list-style-type: none">• HD-TVI : 8.0 Mpx - 3840 x 2160, 5.0 Mpx - 2592 x 1944, 4.0 Mpx - 2560 x 1440, 3.0 Mpx - 1920 x 1536, 1080p - 1920 x 1080, 720p - 1280 x 720,• AHD : 5.0 Mpx - 2592 x 1944, 4.0 Mpx - 2560 x 1440, 3.0 Mpx - 1920 x 1536, 1080p - 1920 x 1080, 720p - 1280 x 720,• HD-CVI : 4.0 Mpx - 2560 x 1440, 1080p - 1920 x 1080, 720p - 1280 x 720,• PAL : 960H - 960 x 576,• IP : max. 8.0 Mpx - 3840 x 2160
Recording speed adjustment:	<ul style="list-style-type: none">1 ... 25 fps @ 3840 x 2160 px IP1 ... 8 fps @ 3840 x 2160 px1 ... 12 fps @ 2560 x 1944 px1 ... 15 fps @ 2560 x 1440 px1 ... 18 fps @ 1920 x 1536 px1 ... 25 fps @ 1920 x 1080 px1 ... 25 fps @ 1280 x 720 px1 ... 25 fps @ 704 x 576 px1 ... 25 fps @ 640 x 480 px for each channel
Operation modes:	Firmware V3.5.37 build 180801 • 16 x HD-TVI / AHD / HD-CVI / PAL / IP + 16 x IP
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	2 x 10 TB SATA
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow.

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Bitrate:	32 ... 10240 kbps
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 or Hik-Connect iOS (iPhone): Free application iVMS-4500 or Hik-Connect
Alarm inputs / outputs:	16 / 4
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones 22 x 18 motion zones
Main features:	Intelligent image analysis : crossing the line (tripwire), intrusion, scene changing
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V / 5 A DC (power adapter included)
Max. power consumption:	≤ 25 W (without HDD)
Color:	Black
Weight:	2.08 kg
Dimensions:	380 x 330 x 52 mm
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	Hikvision
SAP Code:	300219534
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------