

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR APTI-XB3208-S4 32 CHANNELSNet: **335.14 EUR** Gross: **412.22 EUR**

The APTI-XB3208-S4 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.

Attention! The APTI-XBxxx series recorders are supported by the new BitVision and IVMS320 applications. The device does not work with the FREEIP application.

**SPECIFICATION**

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	32 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS
Audio inputs:	12 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 / H.264
Image records resolutions:	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 1080N - 960 x 1080, 720p - 1280 x 720 • CVBS : 960H - 960 x 576, • IP : max. 8.3 Mpx 4K UHD
Recording speed adjustment:	4K UHD IP @ 1 ... 25 fps 1080N @ 1 ... 15 fps 720p @ 1 ... 15 fps 960H @ 1 ... 22 fps for each channel
Operation modes:	<ul style="list-style-type: none"> • 32 x AHD / HD-CVI / HD-TVI @ 1080N • 30 x AHD / HD-CVI / HD-TVI @ 1080N + 2 x IP @ 4 Mpx (max) ... 2 x AHD / HD-CVI / HD-TVI @ 1080N + 30 x IP @ 4 Mpx (max) • 17 x IP @ 4K UHD (max) • 26 x IP @ 5 Mpx (max) • 32 x IP @ 4 Mpx (max) All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	8 x 8 TB SATA + eSATA 8 TB
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 32 channels in the same time
Network functions:	<ul style="list-style-type: none"> • Network Client Software (iVMS320): live view, playback and backup of the records • IE browser: live view, playback and backup of the records and configuration of the recorder parameters
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Darmowa aplikacja BitVision, Android: Darmowa aplikacja iVMS320 • iOS (iPhone): Darmowa aplikacja BitVision, iOS: Darmowa aplikacja iVMS320

Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 6000
USB:	2 pcs USB 2.0
Alarm inputs / outputs:	—
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	230 V AC
Color:	Black
Weight:	7.4 kg
Dimensions:	440 x 442 x 100 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front panel:



Rear view:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:

