Code: DS-7116HQHI-F1/N

AHD, HD-CVI, HD-TVI, PAL DVR **DS-7116HQHI-F1/N** 16 CHANNELS

Hikvision

Net: 283.67 EUR Gross: 283.67 EUR

The DS-7116HQHI-F1/N digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface) and PAL interface is a professional device applicable in surveillance systems.
The HD-TVI interface allows to transmission of analog video signal via coaxial cable at resolutions up to 1080p. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Video inputs:	16 pcs BNC - HD-TVI / AHD / HD-CVI / CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	2048 x 1536 - 3.0 Mpx, Applies to channels: 1-4, HD-TVI only 1920 x 1080 - 1080p 960 x 1080 - 1080N 1280 x 720 - 720p 960 x 576 - 960H 704 x 576 - 4CIF 640 x 480 - VGA
Maximal total frame rate:	100 fps @ 2048 x 1536 px 192 fps @ 1920 x 1080 px, 400 fps @ 960 x 1080 px, 400 fps @ 1280 x 720 px, 400 fps @ 960 x 576 px 400 fps @ 704 x 576 px 400 fps @ 640 x 480 px
Recording speed adjustment:	1 ... 12 fps @ 2048 x 1536 px - 1080p mode 1 ... 25 fps @ 2048 x 1536 px - 1080N mode Applies to channels: 1-4 1 ... 12 fps @ 1920 x 1080 px 1 ... 25 fps @ 960 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px 1 ... 25 fps @ 704 x 576 px 1 ... 25 fps @ 640 x 480 px for each channel

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation modes:	• 4 x HD-TVI max. 3.0 Mpx, 12 fps + 12 x HD-TVI / AHD / HD-CVI / PAL max. 1080p, 12 fps • 4 x HD-TVI max. 3.0 Mpx, 25 fps + 12 x HD-TVI / AHD / HD-CVI / PAL max. 1080N, 25 fps • 16 x 1080p max. 12 fps • 16 x 1080N max. 25 fps • 16 x 720p max. 25 fps
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 16 cameras in the same time
Network interface:	1 x RJ-45 - 10/100/1000 Base-T
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500
Default admin user / password:	admin / -
Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	• rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
Alarm inputs / outputs:	—
PTZ control:	Control compatible with coax HD-TVI Hikvision
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✔
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	White
Weight:	0.91 kg
Dimensions:	285 x 210 x 47 mm
Supported languages:	English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300216497
Guarantee:	**3 years**

PRESENTATION

Top view:



Rear view:



See how to mount a hard disk drive and configure the recorder:
:
In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg

DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60