

Code: APTI-201D2-36WP

IP CAMERA **APTI-201D2-36WP** - 1080p 3.6 mm

Net: **110.40 PLN** Gross: **135.79 PLN**



IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).


PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP66 Index of Protection norm.

SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	3.6 mm, 3 Mpx
View angle:	<ul style="list-style-type: none">• 69 ° (manufacturer data)• 76 ° (our tests result)
S/N ratio:	≥ 52 dB
Range of IR illumination:	20 m
IR illuminator power adjustment:	Automatic
Image compression method:	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Bitrate:	64 ... 12000 kbps
Main stream frame rate:	20 fps @ 1080p
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	<input checked="" type="checkbox"/>
Audio:	<input checked="" type="checkbox"/>
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
WEB Server:	Built-in - port 80
Max. number of on-line users:	10
ONVIF:	2.4

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

RS-485 interface:	
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Darmowa aplikacja FREEIP • iOS (iPhone): Darmowa aplikacja FREEIP
Default admin user / password:	admin / admin
Default IP address:	192.168.1.168
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	<ul style="list-style-type: none"> • WDR - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Possibility to change the resolution, quality and bit rate • BLC - Back Light Compensation • Motion Detection • Privacy zones • Day/night mode • Auto White Balance • Mirror - Mirror image • Sharpness - sharper image outlines
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 260 mA
Power consumption:	≤ 3.2 W
Housing:	Dome, Aluminum
Color:	White
"Index of Protection":	IP66
Operation temp:	-20 °C ... 60 °C
Weight:	0.36 kg
Dimensions:	Ø 110 x 76 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Camera view after remove the Dome cover:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Mounting side view:



Configuration and operation of the FreeIP cloud:

:

In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- Very good image at Full HD quality.
- Small dimensions of the camera.

