

Code: APTI-52V3-2812WP

IP VANDALPROOF CAMERA **APTI-52V3-2812WP** - 5 Mpx 2.8 ... 12 mm

Net: **64.57 EUR** Gross: **79.42 EUR**



IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 2592 x 1944 (5.0 MPx).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.5 " SOI K05 CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx , 2560 x 1920 - 4.9 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p
Lens:	2.8 ... 12 mm, 5 Mpx
View angle:	<ul style="list-style-type: none">• 99 ° ... 32 ° (manufacturer data)• 95 ° ... 38 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	30 m
Memory card slot:	<input type="checkbox"/>
Image compression method:	H.265 / H.264
Main stream frame rate:	25 fps @ 5 Mpx
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	<input type="checkbox"/>
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Audio:	<input type="checkbox"/>
WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	2.4
RS-485 interface:	<input type="checkbox"/>
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Darmowa aplikacja BitVision • iOS (iPhone): Darmowa aplikacja BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:554/0 - Main stream rtsp://user:password@ip_address:554/1 - Sub stream
Main features:	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Possibility to change the resolution, quality and bit rate • ICR - Movable InfraRed filter • Motion Detection • Privacy zones • Mirror - Mirror image • Day/Night mode - configurable • Flicker Control - The technology eliminates the tiring eyes flickering image effect • Sharpness - sharper image outlines
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 520 mA
Power consumption:	≤ 6.2 W
Housing:	Dome - Metal
Color:	White
Vandal-proof:	<input type="checkbox"/>
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.6 kg
Dimensions:	Ø 120 x 97 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION




DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera is out from clamping ring:



Mounting side view:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:

