

Code: DS-2CD2T65FWD-I5(2.8mm)

IP CAMERA **DS-2CD2T65FWD-I5(2.8mm)** - 6.3 Mpx Hikvision

Net: **262.50 EUR** Gross: **322.88 EUR**

IP camera with efficient H.264/H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 6.3 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

Powered by Darkfighter - the camera has very good sensitivity, dedicated to poor lighting conditions.



SPECIFICATION

| | |
|---------------------------|--|
| Standard: | TCP/IP |
| Sensor: | 1/2.4 " Progressive Scan CMOS |
| Scanning system: | Progressive |
| Matrix size: | 6.3 Mpx |
| Resolution: | 3072 x 2048 - 6.3 Mpx , 3072 x 1728 - 5.3 Mpx , 2944 x 1656 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p |
| Lens: | 2.8 mm |
| View angle: | • 99 ° (manufacturer data) • 102 ° (our tests result) |
| Compression: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| S/N ratio: | > 50 dB (AGC off) |
| Range of IR illumination: | 50 m |
| Alarm inputs / outputs: | — |
| Audio: | — |
| Memory card slot: | Micro SD memory cards up to 128GB support (possible local recording) |
| Bitrate: | 32 ... 16384 kbps |
| Main stream frame rate: | 20 fps @ 6.3 Mpx 25 fps @ 5.3 Mpx |
| Network interface: | 10/100 Base-T (RJ-45) |



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------|--|
| Network protocols: | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, IEEE 802.1x, QoS, IPv6, UDP, Bonjour |
| WEB Server: | Built-in, NVR compliance |
| Max. number of on-line users: | 6 |
| ONVIF: | 18.6 |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application iVMS-4500 or Hik-Connect • iOS (iPhone): Free application iVMS-4500 or Hik-Connect |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Default IP address: | 192.168.1.64 |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none"> • Main stream rtsp://192.168.1.64:554/Streaming/Channels/101/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream rtsp://192.168.1.64:554/Streaming/Channels/102/ - RTSP - without authorization rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization |
| RS-485 interface: | — |
| Main features: | <ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines • Intelligent Image Analysis : intrusion, crossing the line (tripwire), abandoned/missing object, scene changing, face detection |
| Power supply: | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 660 mA |
| Power consumption: | <ul style="list-style-type: none"> ≤ 9.5 W @ PoE (802.3af) ≤ 8 W @ 12 V DC |
| Housing: | Compact, Metal |
| "Index of Protection": | IP67 |
| Color: | White |
| Operation temp: | -30 °C ... 60 °C |
| Supported languages: | English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Polish, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Weight: | 1.08 kg |
| Dimensions: | Ø 105 x 290 mm |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 311308164 |



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Guarantee:

3 years

PRESENTATION



Side view:



Camera mounting side view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Bottom view (after remove the cover):



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:

