

Code: APTI-301PC2-36WP

## IP CAMERA **APTI-301PC2-36WP** - 3 Mpx 3.6 mm

Net: **34.05 EUR** Gross: **34.05 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 3 MPx.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. Camera is according to IP66 Index of Protection norm.



### SPECIFICATION

|                                  |                                                                                                              |
|----------------------------------|--------------------------------------------------------------------------------------------------------------|
| Standard:                        | TCP/IP                                                                                                       |
| Sensor:                          | 1/2.7 " Progressive Scan CMOS                                                                                |
| Matrix size:                     | 3 Mpx                                                                                                        |
| Resolution:                      | 2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 720 - 720p                                          |
| Lens:                            | 3.6 mm                                                                                                       |
| View angle:                      | <ul style="list-style-type: none"><li>• 83 ° (manufacturer data)</li><li>• 85 ° (our tests result)</li></ul> |
| S/N ratio:                       | ≥ 52 dB                                                                                                      |
| Range of IR illumination:        | 20 m                                                                                                         |
| IR illuminator power adjustment: | Automatic                                                                                                    |
| Image compression method:        | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                      |
| Bitrate:                         | 64 ... 12000 kbps                                                                                            |
| Main stream frame rate:          | 20 fps @ 3 Mpx                                                                                               |
| Network interface:               | 10/100 Base-T (RJ-45)                                                                                        |
| Alarm inputs / outputs:          | —                                                                                                            |
| Audio:                           | —                                                                                                            |
| Memory card slot:                | —                                                                                                            |
| Network protocols:               | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP                                  |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEB Server:                    | Built-in - port 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Max. number of on-line users:  | 10                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| ONVIF:                         | 2.4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| RS-485 interface:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Mobile phones support:         | Port no.: 80 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BitVision</a><br>• iOS (iPhone): Free application <a href="#">BitVision</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Default admin user / password: | admin / admin                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Default IP address:            | 192.168.1.168                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Web browser access ports:      | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| PC client access ports:        | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Mobile client access ports:    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| RTSP URL:                      | rtsp://user:password@ip_address:80/0 - Main stream<br>rtsp://user:password@ip_address:80/1 - Sub stream                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Main features:                 | <ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ICR - Movable InfraRed filter</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• BLC - Back Light Compensation</li> <li>• Motion Detection</li> <li>• Privacy zones</li> <li>• Day/night mode</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af) - via external PoE stabilizer,</li> <li>• 12 V DC / 330 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Power consumption:             | ≤ 4 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Housing:                       | Compact, Plastic                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Color:                         | White + Black                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| "Index of Protection":         | IP66                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Operation temp:                | -20 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Weight:                        | 0.18 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Dimensions:                    | 164 x 62 x 62 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Supported languages:           | Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Manufacturer / Brand:          | APTI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Guarantee:                     | 2 years                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |

## PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Side view:




Mounting side view:





PoE:



In the kit:



## OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|