

Code: IPC-HFW8231EP-ZH

IP CAMERA **IPC-HFW8231EP-ZH** - 1080p 2.7 ... 12 mm - MOTOZOOM DAHUA

Net: **508.38 EUR** Gross: **508.38 EUR**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition. The used motozoom lens with 2.7 ... 12 mm focal length allows to remote view angle adjustment. Included camera software enables management and integrated monitoring of many network cameras. IVS analysis - crossing the line (tripwire), intrusion, scene changing, abandoned/missing object, face detection, people counting. PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install. The camera is equipped with a built-in heater with a thermostat.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " Progressive Scan Exmor CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p
Lens:	2.7 ... 12 mm - Motozoom
View angle:	• 101 ° ... 36 ° (manufacturer data) • 101 ° ... 35 ° (our tests result)
Compression:	H.265 / H.264 / MJPEG
S/N ratio:	> 50 dB
Range of IR illumination:	50 m
Alarm inputs / outputs:	2 / 1
Bitrate:	• 24 ... 10240 kbps - H.265 • 14 ... 6144 kbps - H.264
Main stream frame rate:	50 fps @ 1080p
Network interface:	100/1000 Base-T (RJ-45)
Default admin user / password:	admin / admin
Network protocols:	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Default IP address:	192.168.1.108

Audio:	• External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Web browser access ports:	80, 37777
PC client access ports:	37777
WEB Server:	Built-in, NVR compliance
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Mobile client access ports:	37777
Max. number of on-line users:	20
Port ONVIF:	80
ONVIF:	2.42
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
RS-485 interface:	—
Main features:	• The camera is equipped with a built-in heater with a thermostat, • WDR - 140 dB - Wide Dynamic Range, • 3D-DNR - Digital Noise Reduction, • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • EIS - Electronic Image Stabilization • ICR - Movable InfraRed filter • D-ZOOM - Digital Zoom • WB - White Balance (ATW/AWB/manual/indoor/outdoor) • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Day/Night mode (color/b&w/auto) • Audio detection • Heat map - the selection in the image by corresponding colors the areas with different traffic • IVS analysis : crossing the line (tripwire), intrusion, abandoned/missing object, face detection, people counting • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • Sharpness - sharper image outlines
Color:	White
Power supply:	• PoE (802.3at), • 12 V DC / 1080 mA
Power consumption:	< 13 W
Housing:	Compact, Metal / Plastic
"Index of Protection":	IP66
Operation temp:	-40 °C ... 60 °C
Weight:	1.17 kg
Dimensions:	274 x 95 x 95 mm
Supported languages:	English, Polish
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:




Bottom view:





Camera mounting side view:




Camera connectors:



In the kit:



Example captures of device interface:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- Motozoom lens.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------