

Code: HAC-HFW2241T-Z-A-27135

AHD, HD-CVI, HD-TVI, PAL CAMERA **HAC-HFW2241T-Z-A-27135** - 1080p
2.7 ... 13.5 mm - **MOTOZOOM** DAHUA
Net: **186.16 USD** Gross: **228.98 USD**

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The "Starlight" series cameras provide a clear color image even at very poor lighting.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

Standard changes are made using configuration switches. Camera is according to IP67 Index of Protection norm.



SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/2.8 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p , 960 x 576 - 960H, PAL
IR illuminator support:	ICR - Movable InfraRed filter
Video output:	AHD, HD-CVI, HD-TVI, CVBS - 1 Vpp / 75 Ω
Lens:	2.7 ... 13.5 mm - Motozoom
View angle:	• 109 ° ... 29 ° (manufacturer data) • 104 ° ... 29 ° (our tests result)
S/N ratio:	> 65 dB
Audio:	• Microphone built-in - HD-CVI only • External microphone input - HD-CVI only
Range of IR illumination:	80 m
IR illuminator power adjustment:	Automatic
OSD menu:	OSD menu available via DAHUA recorder
Main features:	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones • Motion Detection • Mirror - Mirror image • Sharpness - sharper image outlines

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Power supply:	12 V DC / 680 mA
Power consumption:	≤ 8.2 W
Housing:	Compact, Aluminum
Color:	White
"Index of Protection":	IP67
Operation temp:	-30 °C ... 60 °C
Weight:	0.78 kg
Dimensions:	244 x 90 x 90 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION


Front view:



Side view:




Mounting side view:



Standard changes are made using configuration switches:



Camera dimensions:



In the kit:



OUR TESTS

AHD:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at direct strong light opposite to camera:



HD-CVI:


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



HD-TVI:

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:

