

Code: LE-403355

CIRCUIT BREAKER **LE-403355** ONE-PHASE 10 A B TYPE LEGRAND

Net: **9.46 PLN** Gross: **11.64 PLN**

Thermal-magnetic circuit breaker with B-type curve and 10A rated current. The LE-403355 circuit breaker is compatible to DIN TS-35 rail mounting system. Circuit breakers with B-type breaking curve are designed to protection against short-circuits and overloads of the lighting, control circuits and outlets.



SPECIFICATION

Device type:	Circuit Breaker, One-phase
Rated current:	10 A
Number of poles:	1
Tripping curves:	B type
Breaking capacity:	6000 A
Rated voltage:	<ul style="list-style-type: none">• 230 V AC / 50 Hz• 400 V AC / 50 Hz
Connectors type:	screw terminals
Main features:	<ul style="list-style-type: none">• Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls• No possibility of connecting the residual-current blocks• Provided space for a label with description• Can be connected with using the supply busbars fork-type or prong-type
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	1
Weight:	0.104 kg
Dimensions:	83 x 74 x 17.5 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years


PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Side view:




Mounting side view:



Bottom view:



Tripping curves:



1. Tripping time (s)
2. The multiplier of the rated current