


Code: LE-403360

# CIRCUIT BREAKER LE-403360 ONE-PHASE 32 A B TYPE LEGRAND

Net: 6.66 EUR Gross: 6.66 EUR

Thermal-magnetic circuit breaker with B-type curve and 32A rated current. The LE-403360 circuit breaker is compatible to DIN TS-35 rail mounting system. Circuit breakers with B-type breaking curve are designed to protection against short-circuits and overloads of the lighting, control circuits and outlets.



## SPECIFICATION

Device type:	Circuit Breaker, One-phase
Rated current:	32 A
Number of poles:	1
Tripping curves:	B type
Breaking capacity:	6000 A
Rated voltage:	<ul style="list-style-type: none"><li>• 230 V AC / 50 Hz</li><li>• 400 V AC / 50 Hz</li></ul>
Connectors type:	screw terminals
Main features:	<ul style="list-style-type: none"><li>• Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls</li><li>• No possibility of connecting the residual-current blocks</li><li>• Provided space for a label with description</li><li>• Can be connected with using the supply busbars fork-type or prong-type</li></ul>
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	1
Weight:	0.136 kg
Dimensions:	83 x 74 x 17.5 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years

## PRESENTATION




DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



Side view:



Mounting side view:






Bottom view:



Tripping curves:



1. Tripping time (s)
2. The multiplier of the rated current

**PACKAGE**

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

