


Code: LE-403403

## CIRCUIT BREAKER **LE-403403** THREE-PHASE 20 A B TYPE LEGRAND

Net: **46.44 PLN** Gross: **57.12 PLN**

Thermal-magnetic circuit breaker with B-type curve and 20A rated current. The LE-403403 circuit breaker is compatible to DIN TS-35 rail mounting system.

Circuit breakers with B-type breaking curve are designed to protection against short-circuits and overloads of the lighting, control circuits and outlets.



### SPECIFICATION

Device type:	Circuit Breaker, Three-phase
Rated current:	20 A
Number of poles:	3
Tripping curves:	B type
Breaking capacity:	6000 A
Rated voltage:	400 V AC / 50 Hz
Connectors type:	screw terminals
Main features:	<ul style="list-style-type: none"><li>• Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls</li><li>• No possibility of connecting the residual-current blocks</li><li>• Can be connected with using the supply busbars fork-type or prong-type</li><li>• Provided space for a label with description</li></ul>
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	3
Weight:	0.33 kg
Dimensions:	53 x 83 x 75 mm
Manufacturer / Brand:	LEGRAND
Guarantee:	2 years


### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60


Front view:



Side view:




Mounting side view:



Bottom view:



Tripping curves:



1. Tripping time (s)
2. The multiplier of the rated current