


Code: HN-B32/3

CIRCUIT BREAKER **HN-B32/3** THREE-PHASE 32 A B TYPE EATON

Net: **18.39 EUR** Gross: **18.39 EUR**

Thermal-magnetic circuit breaker with B-type curve and 32A rated current. The HN-B32/3 circuit breaker is compatible to DIN TS-35 rail mounting system.

Circuit breakers with B-type breaking curve are designed to protection against short-circuits and overloads of the lighting, control circuits and outlets.



SPECIFICATION


Device type:	Circuit Breaker, Three-phase
Rated current:	32 A
Number of poles:	3
Tripping curves:	B type
Breaking capacity:	6000 A
Rated voltage:	• 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type:	screw terminals
Wire gauge:	1 mm ² - 25 mm ²
Main features:	• Contact position indicator • Possibility of sealing
Housing:	Plastic, DIN, TS-35 rail mounting
Width in 17.5 mm modules:	3
Weight:	0.322 kg
Dimensions:	52.5 x 84.5 x 73 mm
Manufacturer / Brand:	EATON
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Front view:



Mounting side view:



Tripping curves:



1. Tripping time (s)
2. The multiplier of the rated current

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------