

Code: PSB-754813

BUFFERED POWER SUPPLY ADAPTER **PSB-754813** PULSAR

Net: **29.29 EUR** Gross: **36.03 EUR**

The buffer PSU is intended for an uninterrupted supply to devices that require 48V DC (+/-15%).
Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current. Please pay attention for proper cooling conditions of the power adaptor during work!




SPECIFICATION

Adapter type:	Switching
Power voltage:	176 V ... 264 V AC
Output voltage:	<ul style="list-style-type: none">• 44 ... 54 V DC (buffer operation),• 38 ... 54 V DC (battery operation)
Output voltage adjustment:	48 ... 55 V
Maximal load:	1 A + 0.3 A (battery charging)
Output power:	75 W (max)
Efficiency:	88 %
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none">• Short-circuit• Overvoltage• Overvoltage• Overload protection
Operation temp. / Relative humidity:	-10 °C ... 40 °C / 20 % ... 90 %
Weight:	0.47 kg
Dimensions:	159 x 97 x 42 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years


PRESENTATION

Adapter connectors:


DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors:



Schematic diagram:



- 1. Receiver
 - 2. Batteries
- In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

