

Code: MDR-40-48

SWITCHING ADAPTER **MDR-40-48** MEAN WELL

Net: **30.37 EUR** Gross: **30.37 EUR**

Switching adaptor installed on the TS35/7.5 or 15 DIN rail.



SPECIFICATION

Adapter type:	Switching
Power voltage:	85 ... 264 V AC / 120 ... 370 V DC
Output voltage:	48 V DC
Output voltage adjustment:	48 ... 56 V
Voltage tolerance:	$\pm 1 \%$
Maximal load:	0.83 A
Output power:	39.8 W
Number of outputs:	2 pcs
Efficiency:	88 %
Housing type:	DIN
MTBF (Mean Time Between Faults):	min. 301700 hours
Vibration resistance:	IEC60068-2-6, 10 ... 500 Hz max. 2 G
Protections:	• Short-circuit • Overvoltage • Overload protection
Operation temp. / Relative humidity:	-20 °C ... 70 °C / 20 % ... 95 %
Weight:	0.26 kg
Dimensions:	40 x 100 x 90 mm

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


Manufacturer / Brand:	MEAN WELL
Guarantee:	3 years

PRESENTATION

Front panel:



Adapter connectors:




Side view:



Rear panel (DIN rail installation):



Dimensions:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------