

Code: APTI-RF51C2-36W

IP CAMERA **APTI-RF51C2-36W** Wi-Fi - 5 Mpx 3.6 mm APTI

Net: **65.04 EUR** Gross: **80.00 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera.

The used Wi-Fi module allows to remote communication with camera for max. distance up to 300 m. Camera is according to IP67 Index of Protection norm.



SPECIFICATION

| | |
|---------------------------|--------------------------------------------------------------------------------------------------------------|
| Standard: | TCP/IP |
| Sensor: | 1/2.5 " Sony CMOS IMX323 |
| Matrix size: | 5 Mpx |
| Resolution: | 2592 x 1944 - 5 Mpx , 2560 x 1920 - 4.9 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p |
| Lens: | 3.6 mm |
| View angle: | <ul style="list-style-type: none">• 77 ° (manufacturer data)• 82 ° (our tests result) |
| Range of IR illumination: | 30 m |
| Audio: | External microphone input |
| RS-485 interface: | — |
| Alarm inputs / outputs: | — |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Main stream frame rate: | 20 fps @ 5 Mpx 25 fps @ 3.7 Mpx |
| ONVIF: | 2.4 |
| Network protocols: | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network interface: | 10/100 Base-T (RJ-45), Wi-Fi IEEE 802.11 b/g/n |
| Mobile phones support: | Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application BitVision • iOS (iPhone): Free application BitVision |
| Default IP address: | 192.168.1.168 |
| Default admin user / password: | admin / admin |
| Web browser access ports: | 80 |
| PC client access ports: | 80 |
| Web browser access ports: | 80 |
| Mobile client access ports: | 80 |
| Port ONVIF: | 80 |
| RTSP URL: | rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream rtsp://user:password@ip_address:80/2 - Sub stream 2 |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Main features: | <ul style="list-style-type: none"> • Wi-Fi Module - IEEE 802.11 b/g/n, Range : 300 m (open area) • 3D-DNR - Digital Noise Reduction • Flicker Control - The technology eliminates the tiring eyes flickering image effect • BLC - Back Light Compensation • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Built-in Infra-Red illuminator enables night monitoring • ICR - Movable InfraRed filter • Motion Detection • Configurable Privacy Zones • Possibility to change the resolution, quality and bit rate • Sharpness - sharper image outlines • RESET button - on the cable |
| Power supply: | 12 V DC / 360 mA |
| Power consumption: | ≤ 4.3 W |
| Housing: | Metal - Compact |
| "Index of Protection": | IP67 |
| Vandal-proof: | — |
| Weight: | 0.35 kg |
| Dimensions: | Ø 73 x 155 mm |
| Operation temp: | -20 ... 60 °C |
| Supported languages: | Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian |
| Manufacturer / Brand: | APTI |
| Guarantee: | 2 years |

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



Wall mounting side view:



Memory card slot:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|