

Code: IPC-L26P-IMOU

## IP CAMERA **IPC-L26P-IMOU** Wi-Fi Floodlight Cam - 1080p 2.8 mm

Net: **115.74 EUR** Gross: **142.36 EUR**

The cameras of the IMOU series have been designed with special care to simplify the configuration and operation. In combination with the user friendly IMOU platform, the IMOU series devices allow anyone to create a simple and effective surveillance system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 100 m.

Camera is according to IP65 Index of Protection norm.

**Attention!** The IMOU series devices do not have a WEB interface.



### SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.7 " Progressive Scan CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm
View angle:	114 °
White light LED illuminator range:	10 m
Audio:	<ul style="list-style-type: none"><li>• Microphone built-in,</li><li>• Speaker built-in,</li><li>• Bi-directional audio streaming support</li></ul>
Image compression method:	H.265 / H.264
Main stream frame rate:	25 fps @ 1080p
Network protocols:	TCP, DHCP
ONVIF:	—
Network interface:	Wi-Fi - IEEE 802.11 b/g/n
Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">IMOU</a></li><li>• iOS (iPhone): Free application <a href="#">IMOU</a></li></ul>
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	DHCP

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
WEB Server:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 256GB support (possible local recording)
Main features:	<ul style="list-style-type: none"> <li>• Wi-Fi module - IEEE 802.11 b/g/n, Range : 100 m (open area),</li> <li>• LED illuminators : 2000 lm, Operation modes : manual, twilight and motion activated - PIR detector,</li> <li>• Built-in alarm siren : 110 dB,</li> <li>• PIR detector - Built-in, Indoor coverage area 270 ° @ 10 m</li> </ul>
Power supply:	230 V AC
Power consumption:	< 40 W
"Index of Protection":	IP65
Operation temp:	-30 °C ... 50 °C
Weight:	2 kg
Dimensions:	317 x 237 x 172 mm (with bracket)
Supported languages:	—
Manufacturer / Brand:	DAHUA
Guarantee:	2 years

## PRESENTATION



Memory card slot and "Reset" button:




Side view:



Bottom view:



Bottom view (after remove the cover):



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60