

Code: MAGIC-RUBBER-10

TWO-COMPONENT RUBBER **MAGIC-RUBBER-10** RayTech

Net: **797.67 USD** Gross: **981.13 USD**

The MAGIC-RUBBER-10 two-component rubber is intended to protect electronic circuits and electrical connections against external factors.

Thanks to the liquid consistency immediately after mixing the ingredients, the preparation will perfectly protect even complicated circuits, and it can also fill the entire housing of the device, or a junction box. After setting, the product transforms into a hard, slightly elastic rubber, perfectly adhering to components, wires and housing, or junction box.

This product is an excellent protection against solid contaminants, moisture penetration and, thanks to its flexibility, it can also absorb shocks.

The MAGIC-RUBBER-10 rubber is also suitable for making casts and molds for castings.




SPECIFICATION

Voltage insulation:	≥ 23 kV / mm
Package capacity:	2 x 5 l
Main features:	<ul style="list-style-type: none">• Application : The product is dedicated to protecting electrical connections and electronic circuits, The product is also suitable for making casts and molds,• Color : Graphite
Operation temp:	-60 °C ... 200 °C
Weight:	10.9 kg (total)
Dimensions:	245 x 195 x 160 mm - 2 pcs
Manufacturer / Brand:	RayTech
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Example of use with MAGIC-RUBBER-10 profile module:



Preparation method:

:

In the kit:

