

Code: UT650EG/UPS

UPS **UT650EG/UPS** 650 VA CyberPower

Net: **52.69 EUR** Gross: **52.69 EUR**

The UT650EG/UPS UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The patented GreenPower UPS™ Bypass design achieves ultra-low power consumption to reduce energy costs, and allows a lower operation temperature which extends battery lifespan.



SPECIFICATION

Nominal power:	360 W
Apparent Power:	650 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	4 ms (typical)
Charging time (recover to 90% capacity):	6 hours
Estimated battery operation time:	• 30 minutes @ 60 W, • 18 minutes @ 90 W, • 4 minutes @ 180 W
Number of outputs:	3 pcs CEE 7/3 (Schuko)
Protections:	• Glass Fuse • Overvoltage • Overload protection • Overcharge protection • Discharge • Telephone line filter
Operation state indication:	• LED diodes, • Sound signaling

Main features:	• Energy Saving technology - lower energy costs • Automatic Voltage Regulator (AVR) • Compatible with power generators • Built-in EMI, RFI filter • Configurable alarm
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	3.77 kg
Dimensions:	84 x 174 x 280 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------