

Code: AT-UPS600-LED

UPS AT-UPS600-LED 600 VA EAST

Net: 151.11 PLN Gross: 185.87 PLN

The AT-UPS600-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



SPECIFICATION

| | |
|--|--|
| Nominal power: | 360 W |
| Power: | 600 VA |
| Input voltage: | 162 V ... 295 V AC |
| Input frequency: | 50 / 60 Hz (auto detection) |
| Output voltage: | 230 V AC \pm 10 % (Approximated Sine Wave) |
| Output frequency: | 50 / 60 Hz \pm 1 % |
| Transfer time: | 2 ... 7 ms (typical), max. 10 ms |
| Charging time (recover to 90% capacity): | 8 hours |
| Battery: | 1 pcs - 12V/7Ah |
| Backup time: | 10 ... 20 minutes - depending on the load |
| Number of outputs: | 2 pcs CEE 7/3 (Schuko) |
| Protections: | <ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• Overcharge protection• Discharge |
| Operation state indication: | <ul style="list-style-type: none">• LED diodes,• Sound signaling |
| Main features: | <ul style="list-style-type: none">• Automatic Voltage Regulator (AVR)• Configurable alarm• COLD START: - Cold start of the power adapter |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

| | |
|--------------------------------------|--|
| Application: | <ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment |
| Housing type: | Tower |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 % |
| Weight: | 4.24 kg |
| Dimensions: | 300 x 100 x 142 mm |
| Manufacturer / Brand: | EAST |
| Guarantee: | 2 years |

PRESENTATION

Front view:



Rear view:

