

Code: UT1050EG-FR/UPS

UPS **UT1050EG-FR/UPS** 1050 VA CyberPower

Net: **110.01 EUR** Gross: **110.01 EUR**

The UT1050EG-FR/UPS is a professional device, which providing stable power to connected sets of equipment.

The UPS UT CyberPower series has been equipped with the best-in-class housing of fireproof plastic, which provides outstanding fire resistance and helps to minimize possible losses in the case of fire.



SPECIFICATION

Nominal power:	630 W
Power:	1050 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	4 ms
Typical battery charge time:	6 hours
Backup time:	<ul style="list-style-type: none">• 65 minutes @ 60 W,• 43 minutes @ 90 W,• 14 minutes @ 200 W
Number of outputs:	4 pcs
Protections:	<ul style="list-style-type: none">• Overvoltage• Overload protection• Overcharge protection• Protection: DSL / Tel / FAX / Modem - RJ11 / RJ45
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Automatic Voltage Regulator (AVR)• Compatible with generators• Built-in EMI, RFI filter• Configurable alarm

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	6.79 kg
Dimensions:	95 x 220 x 307 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

PRESENTATION





Device connectors:

