

Code: UT650EG-FR/UPS

## UPS **UT650EG-FR/UPS** 650 VA CyberPower

Net: **60.04 EUR** Gross: **73.85 EUR**

The UT650EG-FR/UPS UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.



### SPECIFICATION

Nominal power:	360 W
Apparent Power:	650 VA
Input voltage:	165 V ... 290 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	4 ms (typical)
Charging time (recover to 90% capacity):	6 hours
Backup time:	<ul style="list-style-type: none"><li>• 28 minutes @ 60 W,</li><li>• 16 minutes @ 90 W</li></ul>
Number of outputs:	3 pcs
Protections:	<ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li><li>• Overload protection</li><li>• Overcharge protection</li><li>• Phone/Fax/Modem and RJ11/RJ45 (Combo)/Network protection</li></ul>
Operation state indication:	<ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Automatic Voltage Regulator (AVR)</li><li>• Compatible with generators</li><li>• Built-in EMI, RFI filter</li></ul>

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Application:	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 0 ... 90 %
Weight:	3.75 kg
Dimensions:	84 x 174 x 280 mm
Manufacturer / Brand:	CyberPower
Guarantee:	2 years

## PRESENTATION

Front view:



Rear view:

