

Code: AT-UPS1200BK-LED

## UPS AT-UPS1200BK-LED 1200 VA EAST

Net: 273.97 PLN Gross: 336.98 PLN

The AT-UPS1200BK-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



### SPECIFICATION

|  |   |
|--|---|
| Nominal power:                           | 720 W   |
| Power:                                   | 1200 VA   |
| Input voltage:                           | 173 V ... 287 V AC  |
| Input frequency:                         | 50 / 60 Hz (auto detection)   |
| Output voltage:                          | 230 V AC $\pm$ 10 % (Approximated Sine Wave)  |
| Output frequency:                        | 50 / 60 Hz $\pm$ 1 %  |
| Transfer time:                           | 2 ... 7 ms (typical), max. 10 ms  |
| Charging time (recover to 90% capacity): | 8 hours   |
| Battery:                                 | 2 pcs - 12V/7Ah   |
| Backup time:                             | <ul style="list-style-type: none"><li>• 57 minutes @ 100 W,</li><li>• 14 minutes @ 300 W,</li><li>• 8 minutes @ 500 W</li></ul>                             |
| Number of outputs:                       | 3 pcs CEE 7/3 (Schuko)  |
| Protections:                             | <ul style="list-style-type: none"><li>• Glass Fuse</li><li>• Overvoltage</li><li>• Overload protection</li><li>• Overcharge protection</li></ul>            |
| Operation state indication:              | <ul style="list-style-type: none"><li>• LED diodes,</li><li>• Sound signaling</li></ul>   |
| Main features:                           | <ul style="list-style-type: none"><li>• Automatic Voltage Regulator (AVR)</li><li>• Compatible with generators</li><li>• Built-in EMI, RFI filter</li></ul> |

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

|                                      |  |
|--------------------------------------|--|
| Application:                         | <ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul> |
| Housing type:                        | Tower  |
| Operation temp. / Relative humidity: | 0 °C ... 40 °C / 20 ... 90 %   |
| Weight:                              | 8.5 kg   |
| Dimensions:                          | 346 x 173 x 140 mm   |
| Manufacturer / Brand:                | EAST   |
| Guarantee:                           | 2 years  |

## PRESENTATION

Front view:



Rear view:





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60