

Code: AT-UPS850-PLUS

UPS AT-UPS850-PLUS 850 VA EAST

Net: 253.77 PLN Gross: 312.14 PLN



The AT-UPS850-PLUS UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).

SPECIFICATION

Nominal power:	510 W
Power:	850 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Transfer time:	\leq 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/8Ah
Backup time:	<ul style="list-style-type: none">• 23 minutes @ 100 W,• 5 minutes @ 300 W,• 2 minutes @ 500 W
Number of outputs:	6 pcs CEE 7/3 (Schuko)
Protections:	<ul style="list-style-type: none">• Glass Fuse• Overvoltage• Overload protection• Overcharge protection• Telephone line filter
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> • Automatic Voltage Regulator (AVR) • Compatible with generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm
Application:	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Desktop
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	5.6 kg
Dimensions:	280 x 185 x 95 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Top view:



Side view:





Bottom view:



In the kit:





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60